

# The Effectiveness Of Mold Treatments On The Post Katrina Gulf Coast

The Preliminary Findings of the Hope VI Experiment,  
Biloxi, Mississippi, 2006



# History

- 
- Taken directly from the proposal:

"The post-Katrina landscape had a scope and abundance of mold growth that mold abatement experts had never seen before. The large-scale response to this problem was historically slow. Due to lack of research data, governments and major non-profit organizations have balked at devoting resources, conducting inspections, and assuming liability for the mold issue."
- The purpose of the Hope VI Experiment, as explicitly stated in the study proposal, is to **"identify the effectiveness of 4 mold removal methods being used on houses affected by Hurricane Katrina and to determine cost effectiveness and efficiency of the various processes."**
- The following presentation outlines the preliminary findings of the study, and concludes with a recommendation.



■ 4 Processes, Varying Levels of Time, Labor, and Expenses



- 1) **Hands On Network** Cleanup Recommendations
- 2) **Kolopro** Mold Systems & Solutions Chemical-Free, Anti-Static Mold Treatment
- 3) **Mississippi Department of Health** Recommendations
- 4) **LSU** Recommendations for Mold Cleanup





- Process recommended to Hands On over the Fall of 2005 by various mold professionals.
- Considerable visible scoring success in the field. 4 Step Process.

#### **Step 1: Grinding and Scraping**

- Purpose: To physically remove visible, living mold as well as invisible spores from the wood.
- Procedure: Scrape mold off all surfaces of house using wire brushes and angle grinders

#### **Step 2: Vacuuming**

- Purpose: To physically remove dislodged spores from the house
- Procedure: Use a vacuum equipped with a HEPA filter to vacuum every surface in the house

#### **Step 3: Wiping**

- Purpose: To collect any spores that were not removed by vacuuming or grinding and scraping, and remove from the house
- Procedure: Using a rag that has been dampened with an ammonia-based sanitizing solution, hand-wipe every surface in the house

#### **Step 4: Sealing**

- Purpose: To create a surface that inhibits future mold growth
- Procedure: Using a paint primer, paint every wood surface in the house.



# Kolopro Mold Systems

- □ □ ■ □ □ □ □ □ □ ■ □ □ □ □ □ □
- Chemical-free, anti-static method of fogging as an alternative for people with multiple-chemical sensitivities
  - Specifically, use of **trisodium phosphate** derivative that **polymerizes surfaces with a dry encapsulating film** via fog application, debilitating mold membranes on a microscopic level and retarding further growth
- Chemical is applied by fog machines, approximately 10 minutes per room in the building, with appropriate ventilation via fans.
- After fogging is complete, visible mold wiped off with Kolopro Solution



# Mississippi Department of Health Recommendations



- Removal of Moldy Materials
- Soap Cleanup
  - Non-ammonia soap or detergent, in hot water, scrub the entire area affected by mold. Use stiff brush on block walls and uneven surfaces
- Disinfection
  - Use solution of 10% household bleach

# LSU Recommendations for Mold Cleanup

- 
- Clean and Disinfect
  - “Cleaning should remove, not just kill, the mold, because dead spores can still cause health problems.”
  - “Disinfect wall cavities and other materials after cleaning”
- Consider Borate Treatment
  - “Having a professional pest control applicator apply a borate treatment to wood framing can provide resistance to termites, decay and mold.”
  - ReddPest Solutions contracted to apply Boracare with MoldCare to wood following cleaning/disinfecting



# Pre-Experimental Considerations?

- 
- Weather Conditions
  - Weather conditions on given days were qualitatively assessed. A record of temperature and humidity inside and outside units was kept.
- Documentation
  - Before & After Pictures of Every Building Were Retained
- **The Main Idea**
  - The thrust of the Hope VI experiment is based around the idea of volunteer, non-skilled mold removal, and all results should be interpreted with that facet in mind.



# More Pre-Experiment Facts

- 51 Buildings with 1, 2, or 4 housing units
  - All buildings homogeneously prepared for mold removal by the BHA and HOGC interiors crews
  - Each building randomly assigned to one of four experimental groups or a control group
  - Post-experiment, control buildings and fail buildings would be treated by the most successful method






# Non-viable Air Samples

- Collected using a Zefon™ Bio-Pump, calibrated to collect 75 Liter air flow sample into a slit-impaction sampling device
  - Air samples analyzed at Envriomental Microbiology Laboratory, Inc.
  - Outside air samples necessary in order to compare inside to outside spore counts
    - Spore counts vary by day, therefore environmental relativity is crucial for determining scoring
  - In fully mucked post-Katrina homes built in 2004-2005, an inside to outside ratio of 1 or less is ideal.




# Mean Inside/Outside Counts



	Pre-	Post-
<b>Control</b>	<b>2.73</b>	<b>4.87</b>
<b>Hands On</b>	<b>2.28</b>	<b>1.17</b>
<b>Kolo-pro</b>	<b>3.78</b>	<b>2.30</b>
<b>MS Dept. of Hlth.</b>	<b>6.19</b>	<b>1.19</b>
<b>LSU</b>	<b>2.50</b>	<b>1.17</b>


# # Of Pass Buildings



	Pre-	Post-
<b>Control</b>	<b>10%</b>	<b>10%</b>
<b>Hands On</b>	<b>10%</b>	<b>40%</b>
<b>Kolo-pro</b>	<b>0%</b>	<b>60%</b>
<b>MS Dept. of Hlth.</b>	<b>20%</b>	<b>50%</b>
<b>LSU</b>	<b>0%</b>	<b>60%</b>

# What Does This Mean?

- The air samples were *non-viable*, meaning that the spore traps did not distinguish between live and dead spores
- Therefore, spore traps are a snapshot of post-remediation counts at a given moment
- Information needs to be considered along with *viable* sampling methods to predict sustainability of remediation...



# Viable Mold Sampling


- In contrast to air sampling and tape lifts, fungal culture swabs provided information on the number of colony-forming units (or CFUs) that remained on pre-determined areas of growth after remediation.
  - Results on these samples is much more indicative



**HandsOn** NETWORK  
Be The Change. Volunteer.




# Mean Number of CFUs



	Pre-	Post-
Control	33,541	16,107
Hands On	56,438	3,528
Kolo-pro	95,814	13,720
MS Dept. of Hlth.	26,345	6,948
LSU	51,893	809

# Percent of Buildings With 500 CFUs or Less



TreatmentStatus  
■ Pre-Treatment  
■ Post-Treatment


	Pre-	Post-
<b>Control</b>	<b>0%</b>	<b>10%</b>
<b>Hands On</b>	<b>0%</b>	<b>70%</b>
<b>Kolo-pro</b>	<b>0%</b>	<b>0%</b>
<b>MS Dept. of Hlth.</b>	<b>0%</b>	<b>0%</b>
<b>LSU</b>	<b>0%</b>	<b>80%</b>

# Tape Lifts


- 
- Additional non-viable tests were taken utilizing direct microscopic examination methods
- EMLab Scoring Method
  - <1+ → Very Light Growth
  - 1+ → Light Growth
  - 2+ → Moderate Growth
  - 3+ → Heavy Growth
  - 4+ → Very Heavy Growth



# Mean Visibility Scoring of Penicillium



# Mean Visibility Scoring of Trichoderma



# Conclusions

- Bleach and Fog proved erratic in their effectiveness; some houses hugely successful, most huge failures
  - Much more successful were wire-brushing and non-ammonia sanitization, followed by either Kilz or Boracare
  - Boracare's advantages:
    - Three times as effective at viable CFU reduction as Kilz
    - Is highly soluble, penetrates wood to eradicate internal fungal rot that Kilz can't reach
    - As a sealant, Kilz can incubate moisture in wood, accelerating rot issues and leading to structural failure
  - Boracare's disadvantages:
    - Varied state-by-state pesticide application laws create additional step for relief groups desiring to apply Boracare with Moldcare
    - Cost and accessibility...



# Cost/Benefit Analysis

- Costs of process are equivalent for Hands On method and LSU method **up to sealant application.**
- Cost Comparison for Sealant:

Product	Retail Cost per Gallon	Cost for 4,000 sq. ft.
<i>Kilz 2 Latex Paint Primer</i>	\$39.46	\$157.84
<i>Boracare Pesticide Application</i>	\$83.75	\$418.75



# Conclusions

- In the situation of immediate disaster response, **Boracare** with **Moldcare** is the most effective long-term solution for mold abatement
  - However, given cost constraints and attainability of product, **Hands On**'s process using a latex paint sealant is a viable alternative for remediation
  - In either case, the **MS Department of Health** and **Kolopro** methods of mold remediation are not effective alternatives.
  - If there are any additional inquiries, please direct to [Guillermo Olivos](#), Primary Investigator.

